

Maintenance Oil

another product from vesting lab.



Vesting Maintenance Oil is intended for the maintenance of wooden surfaces treated with oil or (hard) wax oil and ensures an excellent protective layer. You prevent wear on heavy traffic areas, which remain fully protected against moisture and dirt. This product is very suitable to freshen up a floor regularly or to maintain heavy traffic areas. Also suitable for local touching up of scratches and wear and tear to the floor.

Vesting provides all necessary maintenance, cleaning, servicing and repair items which are necessary to support wooden surfaces treated with (hard) wax oil or UV-oil.

Products for excellent abrasion, scratch and water resistance.



Vesting Maintenance Oil is also part of the Vesting Maintenance Package

CHARACTERISTICS

- Contributes to the maintenance of the wear layer
- Dirt and moisture resistant
- Preservation of the original, natural and fresh look of the wooden surface

APPLICATIONS

- For surfaces treated with (hard) wax oil or UV oil
- Also easy to use locally without gloss differences

QUALITIES

- Universal maintenance oil which can be used on all wooden surfaces treated with UV-oil or (hard) wax oil.

COLORS

- Natural
- White

PACKAGING

- 20 x 1 liter
- 4 x 2,5 liter
- 4 x 5 liter

DIRECTIONS FOR USE

Before use: Remove dust from the surface to be treated. Shake the oil can well before use.

Application: Apply with a brush or cloth. Apply Maintenance Oil very thin and uniform, removing excess oil immediately with a lint-free cloth. Do not allow excess oil to dry.

Care instructions
2x a year. More often if the situation requires.

Drying time
Max. 6-12 hours at a temperature between 15 to 20 degrees Celsius.

Coverage
Between 80-100 m² per liter.

Storage
Dry and cool.